

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
25 January 2001 (25.01.2001)

PCT

(10) International Publication Number  
WO 01/06285 A2(51) International Patent Classification<sup>7</sup>: G02B 6/10

(21) International Application Number: PCT/DK00/00407

(22) International Filing Date: 17 July 2000 (17.07.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
PA 1999 01040 16 July 1999 (16.07.1999) DK(71) Applicant (for all designated States except US): HYBRID  
MICRO TECHNOLOGIES APS [DK/DK]; COM Cen-  
ter DTU, Akademivej 349, DK-2800 Lyngby (DK).

(72) Inventors; and

(75) Inventors/Applicants (for US only): KUHMAN, Jochen, F. [DE/DK]; Uglevej 9, 4. tv., DK-2400 Copenhagen NV (DK). POULSEN, Mogens, Rysholt [DK/DK]; Nordre Frihavsgade 57, 4. th., DK-2100 Copenhagen Ø (DK).

(74) Agent: PLOUGMANN, VINGTOFT &amp; PARTNERS A/S; Sankt Annæ Plads 11, P.O. Box 3007, DK-1021 Copenhagen K (DK).

(81) Designated States (national): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KR (utility model), KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

## Published:

— Without international search report and to be republished upon receipt of that report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: HYBRID INTEGRATION OF ACTIVE AND PASSIVE OPTICAL COMPONENTS ON AN SI-BOARD



(57) Abstract: The present invention relates to an assembly structure and a method for assembling active and passive photonic and/or optoelectronic devices on a silicon board. The invention relates in particular to an assembly structure and a method for aligning the photonic devices during the assembling procedure. According to the present invention, the assembly structure comprises one or more alignment features comprising tapered side surface parts in directions at least substantially parallel to an optical axis. By providing a tapering in a direction at least substantially parallel to the first optical axis, any inaccuracies primarily affects the non-critical positioning in the direction along the optical axis, whereas the critical positioning transverse to the optical axis merely depends on the symmetry of alignment features. The errors from the inherent inaccuracy of the position and shape of alignment features are thereby minimised. Also, the de-

vices to be aligned are preferably arranged on top of the alignment features which forms part of the basic structure on the silicon board. All alignment features can thereby be defined in a single mask step together with the structures with which the alignment is to be carried out, resulting in an improved accuracy of the assembly structure. The resulting components will be used especially for broadband telecommunication components.